



Insulation lacing anchor details

photos	material	specification
	<p>Stainless steel 304, stainless steel316, mild steel</p> <p>Surface treatment : polish,zinc plated, copper plated</p>	<p>Pin diameter:1.8mm-3mm Round base with hook 22mm diameter, 1mm thickness, hook length10mm, hook width5mm Pin length:30mm-250mm Face with NO &AB</p>
	<p>Stainless steel 304, stainless steel316, mild steel</p> <p>Surface treatment : polish,zinc plated, copper plated</p>	<p>Pin diameter:1.8mm-3mm Round base with hook 30mm diameter, 1mm thickness, hook length15mm, hook width6mm Pin length:63.5mm-250mm</p>
	<p>Stainless steel 304, stainless steel316, mild steel</p> <p>Surface treatment : polish,zinc plated, copper plated</p>	<p>Pin diameter:1.8mm-3mm Round base with hook 22mm diameter, 1mm thickness, hook length10mm, hook width5mm Pin length:30mm-250mm Face no makes</p>
	<p>Galvanized steel, stainless steel304/316, special is aluminum alloy</p> <p>Surface treatment:polish, spray white color or black color</p>	<p>Common size: Diameter:22mm, 28mm and 38mm Height:7mm-14mm Center hole of Self locking washer is from 1.7mm-2.9mm</p>
	<p>Stainless steel 304/316</p> <p>Surface treatment: polish or plated</p>	<p>Two types: O ring and D ring O ring size:4x40mm D ring size:4mmx28mm Can be customized</p>

	<p>Galvanized steel, Carbon steel, stainless steel 304, stainless steel316</p>	<p>Two types: round type and square type Round type common size:15mm-65mm Square type:20mm-65mm Thickness:0.4mm-1mm</p>
	<p>Galvanized steel, Carbon steel, stainless steel 304, stainless steel316</p>	<p>Round type common size:20-30mm Thickness:1mm</p>
	<p>Galvanized steel Stainless steel 304 Stainless steel 316</p>	<p>Diameter size:22-30mm Thickness:1mm</p>